



Soft Bone Drill Usage Guide

	Tapered Drills																		
DLS-35-8	DLS-35-10	DLS-35-11.5	DLS-35-13	DLS-35-16	DLS-43-8	DLS-43-10	DLS-43-11.5	DLS-43-13	DLS-43-16	DLS-50-8	DLS-50-10	DLS-50-11.5	DLS-50-13	DLS-50-16	DLS-60-8	DLS-60-10	DLS-60-11.5	DLS-60-13	DLS-60-16
035×85	(a) 015 X 10 S	[5] 000 K 111 S 5	200 X 10 8	O. O. D. A. L. B.	E SONETO	PARXIDE TO	C. 648X1156	043X135	OK 3118 X 18	G OSO X DS	II. SOLVED OF THE STATE OF THE	000×1155	E 840×189	E 801.X0327	L OROXES	801.00.00	SCHAILSE SCHAILSE	E SHXURO	E SOLVESS
1 2 3 4 5 6 7 8 9 0	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 6 7 8 9 10	1 2 3 4 6 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 6 7 8 9 10	1 2 3 4 6 7 8 9 10

Our implant drills are made of hardened Surgical Stainless Steel OR Grade 5 Titanium. These tapered drills can be re-used, provided that they are cleaned adequately and re-sterilized.

The cutting edge however does deteriorate with the number of usages and this is dependent on the hardness of bone, which has great variability. The tapered drills can be used for preparation of 10 Implant sites without significant deterioration.

However if any damage to the cutting edge of the drill is present, or if it appears to be blunt then it should be replaced.





Drill Usage Guide

Тар	Tapered Drills														Taps											
Tapered												Tapered				Cylindrical										
D-L-35-8	D-L-35-10	D-L-35-11.5	D-L-35-13	D-L-35-16	D-L-43-8	D-L-43-10	D-L-43-11.5	D-L-43-13	D-L-43-16	D-L-50-8	D-L-50-10	D-L-50-11.5	D-L-50-13	D-L-50-16	D-L-60-8	D-L-60-10	D-L-60-11.5	D-L-60-13	D-L-60-16	D-TAP-L-35	D-TAP-L-43	D-TAP-L-50	D-TAP-L-60	D-TAP-LS-35	D-TAP-LS-43	D-TAP-LS-50
03.5×8	(Na.5.x 10 B)	03.5x11.5	08:5×13 8	03.5ft.x 16 3	[Ø4.3 x 10 = 3	24.3 x11.5 \$ 13	Ø4.311.x13 = 3	Ø4.3IL×16 =]	E 05×8	(F 05×10 B)	8 5.11.50 1 4 - 14		05×16	(F 8×8	F 068x10 F)	F 5.11.5	F @6×13 3	1 06×16	E SCHAFIC MUNICIPALITY	100 PE-12	(E) specialist (C) (A) (A) (A) (A) (A) (A) (A) (A) (A) (A	E DIABLE DIABLES	E SEE AN ALL 22 2 8 MINISTER	Sept. and at a 2 Sept.	DESIGNATION OF THE PROPERTY OF
1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 9	1 2 3 4 4 5 6 6 7 8 9 9 10	1 2 3 4 5 6 7 8 9 9 10	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9	1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 9 10	1 2 3 4 5 6 7 8 9 9 10

Our implant drills are made of hardened Surgical Stainless Steel OR Grade 5 Titanium. These tapered drills and taps can be re-used, provided that they are cleaned adequately and re-sterilized.

The cutting edge however does deteriorate with the number of usages and this is dependent on the hardness of bone, which has great variability. The tapered drills and taps can be used for preparation of 10 Implant sites without significant deterioration.

However if any damage to the cutting edge of the drill is present, or if it appears to be blunt then it should be replaced.